

UV INSTRUMENTS






Protect Yourself

UV radiation is dangerous for unprotected eyes and skin. Users must protect themselves against UV radiation by wearing glasses or face shields. The MP-80 is recommended for protection of the eye and the face. The MP-800 is a face shield with two lateral protections to cover the operator's ears in addition to its eyes and face. Comfortable and efficient, the LP-70 glasses provide total protection to the eyes.

Electromagnetic Spectrum (Enlargement Of Ultraviolet Region)



VILBER's UV Master Technology™

VILBER is the UV fluorescence expert since 1951. Our own UV lamps emit highly concentrated UV radiation. This output is reinforced with the use of our exclusive Ondulex™ reflector, especially polished to reflect the maximum of the light to the outside. Combined with our innovative range of special UV filters, our unique fluorescence sources dramatically improve the quality of gel visualization, documentation and create unrivaled application capabilities.



ISO 9001

VILBER has been approved for registration to ISO 9001:2015. This is an indication of VILBER's commitment towards continuous process improvements and adopting the best practices to consistently exceed customer expectations. An independent registrar ensures that ISO standards are consistently met from year to year and conducts periodic surveillance audits. With several years of ISO compliance and experience, VILBER is proud of its achievement, but never satisfied.

UV TUBES



HIGH UV RADIATION

Thanks to our special lamp glass filters and coating.



LONG LIFETIME

Thousands hours of light.



UNIQUE ELECTRODE

Technology for enhanced reliability.



CONSTANT UV SPECTRUM




Over the complete lifetime.

About UV Tubes

Our original UV tubes emit highly concentrated UV radiation. They use a special ultraviolet ray glass which efficiency transmits the ultraviolet rays. Ultraviolet is located at shorter wavelengths compared to visible light radiation and produces high energy potential

TUBES - 6W TO 40W

Model	Wavelength (nm)	Lenght (mm)
T-40.L	365	1197
T-40.M	312	1197
T-40.C	254	1197
T-30.L	365	892
T-30.C	254	892
T-20.L	365	586
T-20.C	254	586
T-15.L	365	435
T-15.M	312	435
T-15.C	254	435
T-8.L	365	288
T-8.M	312	288
T-8.C	254	288
T-6.L	365	211
T-6.C	254	211





UV LAMPS



UV MASTER TECHNOLOGY

Highly concentrated UV radiations.



EASY TO HANDLE

Lamp stand or holder to add versatility.



LONG LIFETIME

Anodized aluminum housing.



ONDULEX REFLECTOR

Reflect the maximum UV output.

About UV Lamps

Our large choice of filtered and unfiltered lamps range from 6 to 3×40 w-watt.

Our filtered lamps are ideal for the fluorescence detection. The BL-Black-Light lamps provide a large light spectrum with 365nm UV and visible light.

The UV germicidal 254nm lamps help to prevent contamination in research laboratories.

Lamps 6W - Filtered

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
VL-6.LC	365 / 254	145 x 48	2 x 6	UV Fluorescence
VL-6.L	365	145 x 48	1 x 6	UV Fluorescence
VL-6.C	254	145 x 48	1 x 6	UV Fluorescence

Lamps 6W - Unfiltered

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
VL-206.BL	365	No Filter	2 x 6	Black Light
VL-206.G	254	No Filter	2 x 6	Germicidal

Lamps 15W - Filtered

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
VL-215.L	365	295 x 76	2 x 15	UV Fluorescence
VL-215-M	312	295 x 76	2 x 15	UV Fluorescence
VL-215-C	254	295 x 76	2 x 15	UV Fluorescence
VL-115.L	365	295 x 66	1 x 15	UV Fluorescence
VL-115-M	312	295 x 66	1 x 15	UV Fluorescence
VL-115-C	254	295 x 66	1 x 15	UV Fluorescence

Lamps 15W - Unfiltered

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
VL-315-BL	365	No Filter	3 x 15	Black Light
VL-315-G	254	No Filter	3 x 15	Germicidal
VL-215-BL	365	No Filter	2 x 15	Black Light
VL-215-G	254	No Filter	2 x 15	Germicidal
VL-115-BL	365	No Filter	1 x 15	Black Light
VL-115-G	254	No Filter	1 x 15	Germicidal

Lamps 30W -Unfiltered

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
VL-330.BL	365	No Filter	3 x 30	Black Light
VL-330.G	254	No Filter	3 x 30	Germicidal
VL-230.BL	365	No Filter	2 x 30	Black Light
VL-230.G	254	No Filter	2 x 30	Germicidal
VL-130.BL	365	No Filter	1 x 30	Black Light
VL-130.G	254	No Filter	1 x 30	Germicidal

Irradiation Surface For A Height Of About 2m

Power (W)	1 Tube	2 Tubes	3 Tubes
15	1.5 x 2m	1.5 x 3m	1.5 x 4m
20	2m x 2m	2m x 3m	2m x 4m
30	2.5m x 2.5m	2.5m x 3.5m	2.5m x 4.5m
40	3m x 3m	3m x 4m	3m x 5m

Lamps Stands & Handlers

Models	Type	Compatibility
SVL-30	Stand	For VL-115 and VL-215
SVL-6	Stand	For VL-6 and VL-8
SMA	Handle	For VL-6 and VL-8
SMU	Bracket	For VL-6 and VL-8



Lamp Stand Or Holder To Add
Versatility



Highly Concentrated UV
Radiations



Reflect The Maximum
UV Output



UV TABLES



UV MASTER TECHNOLOGY

Highly concentrated UV
radiations.



LONG LIFETIME FILTER

Unlimited life expectancy for
312 & 365nm.



STAINLESS STEEL FRAME

Long lifetime and
no rust.



ADJUSTABLE DUAL INTENSITY

Ideal to switch from short gel
visualization to longer preparative work.

About UV Tables

We provide first-class UV transilluminators for documentation and preparation in different dimensions and configurations. Our innovative Super-Bright filter stops all the visible light emitted by the tubes. As the UV tubes are no more visible, the Super-Bright improves dramatically the quality of gel visualization and documentation.

Transilluminators 8W

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type	Intensity (uW/cm²)
ECX-F26.MX V1	312	210 x 260	5 x 8	UV SuperBright	UV SuperBright
ECX-F26.M V1	312	210 x 260	5 x 8	UV	UV
ECX-F26.C V1	254	210 x 260	5 x 8	UV	UV
ECX-F20.L V1	365	200 x 200	5 x 8	UV	UV
ECX-F20.M V1	312	200 x 200	5 x 8	UV	UV
ECX-F20.C V1	254	200 x 200	5 x 8	UV	UV
ECX-F20.BLUE V1	-	200 x 200	-	Blue Light	Blue Light
ECX-F20.W V1	-	No Filter	5 x 8	White Light	White Light
ECX-F15.M	312	150 x 150	4 x 8	UV	UV
ECX-F15.C	254	150 x 150	4 x 8	UV	UV

Transilluminators 8W - Multiband

Model	Wavelength (nm)	Filter Size (mm)	Power (W)	Type
TCP-26.LMX V1	365 / 312	210 x 260	4 x 8 / 5 x 8	UV SuperBright
TCP-26.LC V1	365 / 254	210 x 260	4 x 8 / 5 x 8	UV
TCP-26.MC V1	312 / 254	210 x 260	4 x 8 / 5 x 8	UV
TCP-20.LM V1	365 / 312	200 x 200	4 x 8 / 5 x 8	UV
TCP-20.LC V1	365 / 254	200 x 200	4 x 8 / 5 x 8	UV
TCP-20.MC V1	312 / 254	200 x 200	4 x 8 / 5 x 8	UV

Conversion Screen

Model	From This Wavelength (nm)	To This Wavelength (nm)	Type
FC-26WL	312	-	White Light



UV DARKROOMS



LARGE CAPACITY

Ideal for small or large sample.



UV ABSORBER SHIELD

Protect the user from the UV light.



COMBINATION OF UV SOURCES

UVA, UVB and UVC can be combined at your convenience.



EASY ACCESS TO DARKROOM

Ideal for mineralogy or TLC plate.

About UV Darkrooms

Our UV darkrooms provide a large effective capacity and a high detection sensitivity. They could offer any combination of UV sources, simultaneously or not. The UV darkroom CN-6 is supplied without lamps and allows different lighting possibilities according to the user's choice.

Darkrooms - 15W

Model	Wavelength (nm)	Power (W)	Type
CN-15	Multichannel darkroom without tubes, chose between the set below		
Set N°1 of 4 tubes	365 / 312	2 x 15 / 2 x 15	UV
Set N°2 of 4 tubes	365 / 254	2 x 15 / 2 x 15	UV
Set N°3 of 4 tubes	312 / 254	2 x 15 / 2 x 15	UV
Set N°4 of 4 tubes	365	4 x 15	UV
Set N°5 of 4 tubes	312	4 x 15	UV
Set N°6 of 4 tubes	254	4 x 15	UV
CN-6	Darkroom without lamp, the wavelengths can be chosen, between 254 nm or 365 nm - VL-6 Models		



White-Light Bulb For Normal
Observation



Removable Lamps That Can Be
Used For Hand-Held Applications



UV RADIOMETERS



PHOTO-ELECTRIC SENSOR

Direct measurement of the UV intensity.



TIME OR ENERGY MEASURE

The intensity is measured in mW/cm^2 and the energy in $\text{joules}/\text{cm}^2$.



MICROPROCESSOR CONTROLLED

Smart and easy to use.



INTERCHANGEABLE SENSOR

Wavelength dependent sensors could be used one at a time.

About UV Radiometers

The radiometers measure UV light intensity for a specific wavelength (254nm, 312nm or 365nm). They are designed for an accurate and direct measurement of the UV radiation. All our radiometers use a silicon photo-electric sensor for a direct measurement of the UV intensity and thus do not convert UV into visible light.

Sensors

Model	Wavelength (nm)	For
CX-365	365	VLX-3W
CX-312	312	VLX-3W
CX-254	254	VLX-3W



Precise, Highly Acurate And User Friendly



Measure the UV radiation dose as a function of time or energy.

BIO-LINK BLX

The Bio-Link crosslinker is an UV irradiation system, mainly dedicated to the linking of nucleic acid to membranes and elimination of PCR contamination. Its innovative design ensures unique features:

- The programmable microprocessor constantly monitors the UV light emission. The irradiation stops automatically when the energy received matches the programmed energy.
- Thanks to its UV sensor, the irradiation cycles are perfectly reproducible, regardless of intensity fluctuation of the UV source. Just programme your energy and Bio-Link delivers it!
- The UV light sensor is positioned above a well of light, in the top of the irradiation chamber. The UV measure is then collected from all the UV tubes and not just from one for enhanced consistency!
- The large number of presets in either energy unit or time unit makes the Bio-Link a very simple instrument to use while very powerful.

KEY FEATURES

- Precise irradiation in either energy (Joules/cm²) or time (seconds)
- Preset programme for dosage of 0.120 J/cm² to optimise nucleic acid linking
- Storage of the last UV setting
- Protective quartz disk on the UV sensor cell
- Spacious UV exposure chamber in stainless steel
- Safety interlock door with UV blocking observation window
- UV wavelengths interchangeable



SPECIFICATIONS

UV source	5 x 8-watt Either in 254nm, 312nm, 365nm
Energy display	Two measurement ranges: <ul style="list-style-type: none"> • from 0.025 to 9.999 Joules • from 0.025 to 99.99 Joules
Exposure time display	Two measurement ranges: <ul style="list-style-type: none"> • from 00.10 to 99.59 Minutes/Seconds • from 000.1 to 599.5 Minutes/Seconds
Manual controls	Manual energy exposure setting Manual time exposure setting
Presets	Energy: 9 presets Exposure Time: 9 presets
Internal dimensions (H x D x W)	14.5 x 33 x 26 cm
External dimensions (H x D x W)	30.5 x 36 x 35 cm
Weight	10.500 kg
Power (voltage / hertz)	230 V / 50-60 Hz 115 V / 60 Hz 100 V / 50-60 Hz



UV MASTER TECHNOLOGY

Highly concentrated UV radiations.



EASY TO HANDLE

Spacious UV exposure chamber in stainless steel.



LONG LIFETIME

Protective quartz disk on the UV sensor cell.



ONDULEX REFLECTOR

Reflect the maximum UV output.

About UV Bio-Sun

The BioSun is a complete, microprocessor controlled UV irradiation system designed for Petri dishes or micro-plates. Based on a programmable microprocessor, the system constantly monitors the UV light emission. The irradiation stops automatically when the energy received matches the programmed energy. Thanks to its advanced UV sensors, the irradiation cycles are perfectly reproducible, regardless of the intensity fluctuation of the UV source. Just program your energy and Bio-Sun delivers it!

FLEXIBILITY

- UVA, UVB or UVA & UVB irradiation
- UVC 254nm germicidal lamps for tray sterilisation
- Silicon photoelectric sensor for direct measurement of the UV intensity

PERFORMANCE

- Scientific grade UV Irradiation system
- Perfectly reproducible UV irradiation cycles
- Highly homogeneous UVA and UVB sources (312 and 365nm)



MULTI-APPLICATIONS

- Data acquisition controlled by micro-processor
- Constant monitoring of the received energy versus the programmed energy T
- Temperature, UV intensity, and time passed supervision

EASY & INTUITIVE

- Powerful cooling system
- Optional software connection for data monitoring and recording
- Fantastic ease of use and maintenance

HEADQUARTERS

Vilber Lourmat
ZAC de Lamirault
Collegien
F-77601 Marne-la-Vallee cedex 3
France
Phone : + 33 (0) 1 60 06 07 71
info@vilber.com

GERMANY

Vilber Lourmat
Deutschland GmbH
Wielandstrasse 2
D-88436 Eberhardzell
Deutschland
Phone : + 49 (0) 7355 931 380
info@vilber.de

CHINA

Vilber China
Room 127 Building A
N° 111 Yuquangying
Fengtai District – Beijing
China
Phone : + 86 1361 1131 545
info@vilber.cn